

YS29AT, Aluminum - Compression Splice

By Burndy
Catalog # [YS29AT](#)



High Voltage Uninsulated Al Tube Compression Splice, 250 kcmil Al Cable, 5.37" L.

General

Catalog Number	YS29AT
Color Code	Red
Connector Type	Splice
Die Index	324
Feature - Barrel Style	Tapered
Feature - Barrel Type	Standard
Material	Aluminum
Physical Attribute - Number of	3
Crimps Required	
Plated	Y
Plating Type	Tin - Electro Plated
Trade Name	HYLINK™
UPC	781810001400
UPC 14 Digit GTIN	00781810001400

Dimensions

Dimension - B Length inch	2.29 in
Dimension - L Length Overall mm	136 mm
Dimension - Length Overall inch	5.37 in
Dimension - Outside Diameter inch	0.92 in
Dimension - Pad Width inch	2.58 in

Dimension - Strip Length inch 2 7/8

Conductor Related

Conductor - AL Str Size 250 kcmil

Certifications And Compliance

Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No

Logistics

Carton Quantity	50
Minimum Pack Quantity	1
Pallet Quantity	7200

Product Assets

- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR_YS-AT_LineArt](#)
- [Sales Drawings - SC..025626-01](#)
- [Specifications - YS29AT](#)