

# YS31, Cu Compression Splice, Long Barrel, 350 kcmil

By Burndy  
 Catalog # [YS31](#)



350 kcmil, CU, Long Barrel SPLICE

## Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

## Application

Wire Splice

## Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

## Conductor

Conductor - Material	COPPER
Wire Size	350 kcmil
Conductor - Copper Str Size	350 kcmil
Conductor - Copper Str Navy Size	350 (91) Navy
Conductor Size	350 KCMIL
Conductor - Copper Str Size Range	350 kcmil
Conductor Type	CODE

## Configuration

Connector Type LONG BARREL

## Current

Voltage - Maximum 35000  
 Voltage Rating 35 kV

## Dimensions

Dimension - L Length Overall mm 110 mm  
 Dimension - Strip Length inch 2-1/16  
 Dimension - B Length inch 1.95 in  
 Dimension - Length Overall inch 4.35 in

## General

Die Index 18  
 Trade Name HYLINK™  
 Sub Brand HYLINK  
 Color Code Red  
 Plated Y  
 Feature - Barrel Type Long  
 Feature - Barrel Style Chamfered  
 Type YS, Long Barrel  
 UPC 12 Digit 781810508251  
 UPC 14 Digit GTIN 00781810508251  
 Material COPPER  
 Plating Type Tin - Electro Plated  
 Finish Type Tin-Plated  
 UPC 781810508251

## Logistics

Minimum Pack Quantity 1  
 Carton Quantity 10

## Product Assets

[Catalog \[English\]](#)