

YS3C, Compression Splice, 3 AWG Cu, Long Barrel

By Burndy
Catalog # [YS3C](#)



3 AWG, CU, Long Barrel SPLICE

Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	#3 AWG
Conductor - Copper Str Size	3 AWG
Conductor - Copper Str Navy Size	50 (19) Navy
Conductor Size	3 AWG
Conductor - Copper Str Size Range	3 AWG
Conductor Type	CODE

Configuration

Connector Type LONG BARREL

Current

Voltage - Maximum 35000
Voltage Rating 35 kV

Dimensions

Dimension - L Length Overall mm 71 mm
Dimension - Strip Length inch 1-5/16
Dimension - B Length inch 1.22 in
Dimension - Length Overall inch 2.80 in

General

Die Index 9
Trade Name HYLINK™
Sub Brand HYLINK
Color Code White
Plated Y
Feature - Barrel Type Long
Feature - Barrel Style Chamfered
Type YS, Long Barrel
UPC 12 Digit 781810507100
UPC 14 Digit GTIN 00781810507100
Material COPPER
Plating Type Tin - Electro Plated
Finish Type Tin-Plated
UPC 781810507100

Logistics

Minimum Pack Quantity 1
Carton Quantity 25

Product Assets

[Catalog \[English\]](#)