

YS44, Cu Compression Splice, Long Barrel, 1000 kcmil

By Burndy
Catalog # YS44



1000 kcmil, CU, Long Barrel SPLICE

Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Industry Standard(s)	No
Buy America(n) Qualified	UL 486A-486B
Certification - ETL	Contact Manufacturer
Standards - Industry Standards Met	No
Standards - RoHS Compliance Status	UL 486A-486B
Certification - CSA Approved	CM
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	1000 kcmil
Conductor - Copper Str Size	1000 kcmil
Conductor Size	1000 KCMIL
Conductor - Copper Str Size Range	1000 kcmil
Conductor Type	CODE

Configuration

Connector Type LONG BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - L Length Overall mm	166 mm
Dimension - Strip Length inch	3
Dimension - B Length inch	2.94 in
Dimension - Length Overall inch	6.55 in

General

Die Index	27
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	White
Plated	Y
Feature - Barrel Type	Long
Feature - Barrel Style	Chamfered
Type	YS, Long Barrel
UPC 12 Digit	781810527603
UPC 14 Digit GTIN	00781810527603
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810527603

Logistics

Minimum Pack Quantity	1
Carton Quantity	3

Product Assets

[Catalog \[English\]](#)