

YSCM27, Seamless Parallel Compression Splice Connector, 16,910-26,890 Circular Mils CU

By Burndy
Catalog # [YSCM27](#)



16,910 - 26,890, Circular Mils, CU, SPLICE

Features

- Copper seamless barrel uninsulated parallel splice
- Designed to accommodate a wide range of stranded wires to be laid parallel inside the barrel and spliced together
- Electro-tin plated unless otherwise specified
- Barrel is color coded to ensure proper die and installation tooling is selected

Application

Wire Splice

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	Yes
Certification - UL Recognized	Yes
Certification - ETL	No
Standards - Industry Standards Met	No
Standards - Industry Standards	UL 486A-486B
Standards - RoHS Compliance Status	CM
Industry Standard(s)	UL 486A-486B
Certification - CSA Approved	No
UL Listed	No
Buy America(n) Qualified	Contact Manufacturer

Conductor

Conductor - Material	COPPER
Conductor Size	16,910-26,890 CMILS
Conductor - Copper Str Size	7 AWG;6 AWG
Conductor - Copper Str Size Range	7 AWG-6 AWG
Conductor Type	CODE
Wire Range	16,910 - 26,890 Circular Mils

Configuration

Connector Type	Splice
----------------	--------

Current

Voltage - Maximum	600 V
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter	0.31 inch
Dimension - L Length Overall	13 mm
Dimension - Strip Length	11/16 inch
Dimension - Length Overall	0.50 inch

General

Sub Brand	HYLINK
Die Index	7
Color Code	Blue
Trade Name	HYLINK™
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Type	YSCM
UPC 12 Digit	781810358504
UPC 14 Digit GTIN	00781810358504
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810358504

Logistics

Minimum Pack Quantity	200
Carton Quantity	200
Pallet Quantity	99999

Product Assets

[Catalog \[English\]](#)