


YSHG3434 Compression H-Tap Connector

By Burndy
Catalog # [YSHG3434](#)

Copper Compression Double H- Tap Connector, 4/0 AWG - 400 kcmil (Tap), # 6 Rebar/ 3/4" Ground Rod/ 400 to 250 kcmil Cu Cable



Features

- UL467 Listed
- Suitable for direct burial in earth or concrete
- High conductivity copper extrusion minimizes resistance and eliminates corrosion due to dissimilar metals
- Grooves are prefilled with PENETROX™ E2 oxide inhibitor and individually sealed inhibiting moisture and contaminants

Application

For Direct Burial In Earth Or Concrete

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 467, Direct Burial
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rebar Run	6
Conductor - Rebar Run Range	6
Conductor - Rod Run	3/4 in
Conductor - Rod Run Range	3/4 in
Conductor - Copper Str Run	250 kcmil;300 kcmil;350 kcmil;400 kcmil
Conductor - Copper Str Run Range	250 kcmil-400 kcmil

Conductor - Copper Str Tap	4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil
Conductor - Copper Str Tap Range	4/0 AWG-400 kcmil

Configuration

Physical Attribute - Number of Crimps Required	4
Connector Type	H-Tap

Dimensions

Dimension - Height mm	0 mm
Dimension - Width inch	2.43 in
Dimension - Width mm	62 mm
Dimension - Length Overall inch	2.44 in

General

Die Index	1104
Trade Name	HYGROUND®
Sub Brand	CRIMPIT
Plated	N
Type	Taps
UPC 12 Digit	781810129692
UPC 14 Digit GTIN	00781810129692
Material	Copper
Plating Type	Unplated
UPC	781810129692

Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	2400

Product Assets

[Catalog \[English\]](#)