

YSM2C, Uninsulated Parallel Splice For 42,613 - 66,832 cmils

By Burndy
Catalog # YSM2C



Uninsulated Parallel Splice For 42,613 - 66,832 cmils.

Features

- Seamless tubing
- Beveled barrel for ease of wire entry
- Tin plated
- Parallel design results in only one crimp necessary
- Uninsulated barrel provides an economical termination solution when insulation is not specified

Application

HYLINK Type YSM seamless parallel splice connector permits wires to be laid parallel inside the connector and spliced together with the BURNDY family of HYTOOL installation tooling

General

Catalog Number	YSM2C
Color Code	Brown
Connector Type	Parallel Splice
Die Index	10
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Material	Copper
Plated	Y
Plating Type	Tin
Sub Brand	HYLINK
Temperature Rating	90
Trade Name	HYLINK™
Type	YSM
UPC	781810805763
UPC 14 Digit GTIN	00781810805763

Dimensions

Dimension - Length Overall inch	0.62 in
Dimension - Outside Diameter inch	0.47 in
Dimension - Strip Length inch	11/16

Conductor Related

Conductor - Copper Solid Size	12 AWG;11 AWG;10 AWG
Conductor - Copper Solid Size Range	12 AWG-10 AWG
Conductor - Copper Str Size	12 AWG;10 AWG
Conductor - Copper Str Size Range	12 AWG-10 AWG
Conductor Size	42,613 - 66,832 cmils
Conductor Type	<ul style="list-style-type: none">• CU C Solid-Size• CU C Str-Size

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - Industry Standards	UL486
Met	
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

Logistics

Carton Quantity	200
Minimum Pack Quantity	1
Pallet Quantity	99999

Product Assets

[3D Models - YSM2C_MODEL-IGES](#)
[3D Models - YSM2C_MODEL-STEP](#)
[3D Models - YSM2C_MODEL-PDF](#)
[Catalogs - BURNDY Master Catalog - Section B - Small Terminals](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Sales Drawings - 50094200](#)
[Specifications - YSM2C](#)