

YSM8C, Uninsulated Parallel Splice For 6,088 - 16,864 cmils

By Burndy
Catalog # YSM8C



Uninsulated Parallel Splice For 6,088 - 16,864 cmils.

Features

- Seamless tubing
- Beveled barrel for ease of wire entry
- Tin plated
- Parallel design results in only one crimp necessary
- Uninsulated barrel provides an economical termination solution when insulation is not specified

Application

HYLINK Type YSM seamless parallel splice connector permits wires to be laid parallel inside the connector and spliced together with the BURNDY family of HYTOOL installation tooling

General

Catalog Number	YSM8C
Connector Type	Parallel Splice
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Material	Copper
Plated	Y
Plating Type	Tin
Sub Brand	HYLINK
Temperature Rating	90
Trade Name	HYLINK™
Type	YSM
UPC	781810805794
UPC 14 Digit GTIN	00781810805794

Dimensions

Dimension - Length Overall inch	0.41 in
------------------------------------	---------

Dimension - Outside Diameter
inch

Dimension - Strip Length inch

Conductor Related

Conductor - Copper Str Size
12 AWG;10 AWG;9 AWG;8 AWG

Conductor - Copper Str Size
Range
12 AWG-8 AWG

Conductor Size
6,088 - 16,864 cmils

Conductor Type
• CU C Solid-Size
• CU C Str-Size

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No

Logistics

Carton Quantity	200
Minimum Pack Quantity	200

Product Assets

[Catalogs - BURNDY Master Catalog - Section B - Small Terminals](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Sales Drawings - 50094200](#)
[Specifications - YSM8C](#)