

Eaton 170M1413

Catalog Number: 170M1413

Fuse-link, high speed, 40 A, AC 690 V, DIN 000, gR, DIN, IEC, single indicator, live gripping lugs



Photo is representative

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M1413
	Model Code
	FUSE 40A 690V 000TN/80 GR UC
UPC	EAN
051712216791	5027590332873
Product Length/Depth	Product Height
100 mm	53 mm
Product Width	Product Weight
21 mm	147.3 g
Warranty	Compliances
Not Applicable	CE Marked
	RoHS Compliant
Certifications	
IEC Rated	
UL Recognized	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

40 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

gR (general purpose semiconductor protection)

Voltage type

AC

Fuse size

000

Rated voltage AC

690 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M8

Class

Class gR

Clearing (I2T)

460 at 660 V

Watt losses

12 W

Fuse shape

Square body, slotted offset bolted tags

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

[170M1413-Eaton Bussmann series high speed square body fuse](#)

Compliance information

[UKCA 170M size 000 10A to 315A](#)

[CE 170M size 000 10A to 315A](#)

Pre arc (I2T)

69

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

000

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

TN/80 Type T Indicator for Micro

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia