

Fuse-link, high speed, 400 A, AC 690 V, compact DIN 1, 45 x 58 x 134 mm, aR, DIN, IEC, type K indicator



defaultTaxonomyAttributeLabel

Type

Fuse

Application

semiconductor protection

Amperage Rating

400 A

Breaking capacity

200 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1*

Rated voltage AC

690 V

Center-to-center distance of connections

106 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I2T)

105000 at 660 V

Watt losses

60 W

Clearing loss

60

Fuse shape

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

[170M3269~Eaton Bussmann series high speed square body fuse](#)

Compliance information

[UKCA Fuse-links for the protection of semiconductor devices, sz1* up to 630A](#)

[CE Fuse-links for the protection of semiconductor devices, sz1* up to 630A](#)

Technical data sheets

[720014 DIN 43653 690V](#)

Square body, slotted center bolted tags

Pre arc (I2T)

15000

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

Other

Mounting method

DIN 43 620

Packaging type

Standard

Voltage rating

690 V

Fuse type

Bolted tag

DIN 43653

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia