

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

700 A

Breaking capacity

200 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1

Rated voltage AC

690 V

Center-to-center distance of connections

108 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I²T)

725000 at 660 V

Watt losses

85 W

Clearing loss

85

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[170M4267~Eaton Bussmann series high speed square body fuse](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA Fuse-links for the protection of semiconductor devices, Size 1 up to 900A](#)

[CE Fuse-links for the protection of semiconductor devices, Size 1 up to 900A](#)

Technical data sheets

[720014 DIN 43653 690V](#)

Fuse shape

Square body, slotted center bolted tags

Pre arc (I2T)

34000

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

1

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

KN/110 Type K Indicator for Micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)