

Eaton C14G4

Catalog Number: C14G4

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 4 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C14G4
	UPC
	051712754330
EAN	Product Length/Depth
5027590494052	51 mm
Product Height	Product Width
14.3 mm	14.3 mm
Product Weight	Warranty
20.3 g	1 year limited
Compliances	Certifications
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

Product specifications

Fuse indicator

Other

Construction size

14 mm x 51 mm

Rated voltage AC

690 V

Connection

Ferrule end x ferrule end

Quantity

10

Current type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Amperage Rating

4 A

Frequency rating - max

62 Hz

Utilization category

gG (cable protection/equipment protection)

Watt losses

1 W

Fuse type

C14G

Type

fuse

Fuse shape

Cylindrical

Resources

Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Breaking capacity

80 kA

Fuse size

14 x 51 mm

Frequency rating - min

45 Hz

Class

Class C gL/gG

Voltage rating

690 V

Application

for industrial applications

for general purpose use

Voltage type

AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)