

Eaton C14G50

Catalog Number: C14G50

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 400 Volts AC, 50 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C14G50
	UPC
	051712754422
EAN	Product Length/Depth
5027590494120	51 mm
Product Height	Product Width
14.3 mm	14.3 mm
Product Weight	Warranty
20.6 g	1 year limited
Compliances	Certifications
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

Product specifications

Fuse indicator

Other

Construction size

14 mm x 51 mm

Rated voltage AC

400 V

Connection

Ferrule end x ferrule end

Quantity

10

Current type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Amperage Rating

50 A

Frequency rating - max

62 Hz

Utilization category

gG (cable protection/equipment protection)

Watt losses

4.8 W

Fuse type

C14G

Type

fuse

Fuse shape

Cylindrical

Resources

Catalogs

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE C08G, C08M, etc cylindrical fuselinks](#)

[UKCA C08G, C08M, etc cylindrical fuselinks](#)

Technical data sheets

[720115 Cylindrical fuses](#)

Breaking capacity

120 kA

Fuse size

14 x 51 mm

Frequency rating - min

45 Hz

Class

Class C gL/gG

Voltage rating

400 V

Application

for industrial applications

for general purpose use

Voltage type

AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia