Eaton Bussmann series FWH high speed fuse

FWH-30A14F

UPC:051712370844

Dimensions:

Height: 14 MMLength: 51 MMWidth: 14 MM

Weight:21.6 G

Warranties:

· Not Applicable

Specifications:

• Type: High speed fuse

 Application: protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters

Voltage Rating: 1000 Vac, 800 Vdc
Voltage Rating Numeric: 500 V

• Amperage Rating: 30A

• Amperage Rating Numeric: 30 A

 Interrupt Rating: 200 kAIC Vac, 50 kAIC at 500 Vdc

• Connection: Ferrule end X ferrule end

Construction Size: 14 x 51 mm
 Packaging Type: Standard

• Breaking Capacity: 200 A

• Clearing (I2T): Clearing at 500V: 232

Frequency Rating Maximum: 62 HZ
 Frequency Rating Minimum: 45 HZ

• Fuse Shape: cylindrical

• Fuse Indicator: Non Indicating

• Pre Arc (I2T): 58

• Release Characteristic: Other

 Utilization category: aR (accompanied semiconductor protection)



Voltage Type: AC/DCWatt Losses: 9WWith Striker: No

Supporting documents:

- Product Catalog
- 30AMP 500V AC FERRULE 6.4 X 31.8MM

Certifications:

- CSA Certified
- UL Recognized

Product compliance:

CE Marked

© 2016 Eaton. All rights reserved.