

Eaton FWH-6A14F

Catalog Number: FWH-6A14F

Eaton Bussmann series FWH high speed fuse, 6A, 200 kAIC Vac, 50 kAIC at 500 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end



Product specifications

Fuse indicator	Interrupt rating
Non Indicating	50 kAIC
Construction size	Clearing (I2T)
14 mm x 51 mm	6.4 at 500 V
Connection	Material
Ferrule end x ferrule end	Ceramic
Release characteristic	Amperage Rating
Other	6 A
Frequency rating - max	Utilization category
62 Hz	aR (accompanied semiconductor protection)
Watt losses	Fuse type
1.5 W	FWH-A14F
Accessories	Type
CH14 Modular fuse holder FW14-PCB	High speed fuse
	Fuse shape
	Cylindrical
	Breaking capacity
	200 kA
Fuse size	Frequency rating - min
14 x 51 mm	45 Hz
Class	Pre arc (I2T)
Class aR	1.6

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc](#)

[UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc](#)

Technical data sheets

[720008 FWH](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia