

Eaton FWJ-60A

Catalog Number: FWJ-60A

Eaton Bussmann series FWJ high speed fuse, 700 Vac (UL), 690 Vac (IEC), 800 Vdc (5-50A), 60A, 25 kAIC (35-200A), 100 kAIC (250-2000A), 50 kAIC at 800 Vdc (35-200A, 450-600A), None, High speed fuse, Blade end X blade end, Stud



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWJ-60A
	UPC
	051712796156
EAN	Product Length/Depth
5027590499828	19 mm
Product Height	Product Width
19 mm	127 mm
Product Weight	Warranty
120 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	CSA Certified

Product specifications

Rated voltage DC

800 V

Interrupt rating

450-600A)

50 kAIC at 800 Vdc (35-200A

100 kAIC (250-2000A)

25 kAIC (35-200A)

Center-to-center distance of connections

106.91 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC/DC

Mounting method

Stud

Amperage Rating

600 A

Fuse type

FWJ-A

Fuse system (according to IEC 60269)

Other

Rated switching capacity

25 A

Voltage rating

1000 Vac, 800 Vdc

Fuse indicator

Non Indicating

Construction size

Other

Clearing (I²T)

5000 at 1000 V

Rated voltage AC

1000 V

Color

None

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Connection

Blade end x blade end

Mounting dimension

M8

Utilization category

aR (accompanied semiconductor protection)

Watt losses

11 W

Type

High speed fuse

Fuse shape

Cylindrical, center bolted tags

Breaking capacity

25 kA

Class

Class aR

Pre arc (I2T)

670

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia