

# Eaton FWP-1A14F

Catalog Number: FWP-1A14F

Eaton Bussmann series FWP high speed fuse, 700V (UL), 1A, 200 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic



Photo is representative

## General specifications

|   |                             |
|---|-----------------------------|
| <b>Product Name</b>                               | <b>Catalog Number</b>       |
| Eaton Bussmann series high speed cylindrical fuse | FWP-1A14F                   |
|   | <b>UPC</b>                  |
|   | 051712795098                |
| <b>EAN</b>  | <b>Product Length/Depth</b> |
| 5027590500272                                     | 51 mm                       |
| <b>Product Height</b>                             | <b>Product Width</b>        |
| 15 mm   | 15 mm                       |
| <b>Product Weight</b>                             | <b>Warranty</b>             |
| 20.6 g  | Not Applicable              |
| <b>Compliances</b>                                | <b>Certifications</b>       |
| CE Marked   | CSA Certified               |
| RoHS Compliant                                    | UL Recognized               |

## defaultTaxonomyAttributeLabel

### Type

High speed fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

1 A

### Accessories

CH14 Modular fuse holder  
FW14-PCB

### Breaking capacity

200 kA

### Frequency rating - max

62 Hz

### Frequency rating - min

45 Hz

### Fuse indicator

Non Indicating

### Release characteristic

Other

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC/DC

### Fuse size

14 x 51 mm

### Class

Class aR

### Clearing (I2T)

0.41

### Watt losses

5.7 W

### Fuse shape

Cylindrical

### Pre arc (I2T)

## Resources

### Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

### Compliance information

CE FWC-\*A10F,FWH-\*A14F,FWP-\*A14F,FWP-\*A14FI etc

UKCA FWC-\*A10F,FWH-\*A14F,FWP-\*A14F,FWP-\*A14FI etc

### Technical data sheets

720025 FWP

0.04

Color

White

Interrupt rating

200 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

700 V

Fuse type

FWP-A14F



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)