

Eaton GDA-500MA

Catalog Number: GDA-500MA

Eaton GDA Series Fast-acting fuse 0.500A, 250 Vac, 32 Vdc (self certified), GDA-500MA

General specifications

Product Name	Catalog Number
Eaton Bussmann series GDA fast-acting fuse	GDA-500MA
	UPC
	051712431248
Product Length/Depth	Product Height
20 mm	5 mm
Product Width	Product Weight
5 mm	0.02 g
Compliances	Certifications
CCC Marked	VDE
RoHS Compliant	
CE Marked	Catalog Notes
	High breaking capacity

Product specifications

Fuse indicator

Non-indicating

Interrupt rating

1.5 kAIC at 250 Vac

Connection

Ferrule end x ferrule end

Quantity

5

Material

Nickel-plated brass end cap construction

Ceramic tube

Melting (I₂T)

Typical: 0.038 A

Amperage Rating

0.500A

Voltage drop

1050 mV typical

Frequency rating - max

50 Hz

Resistance

0.46 ohms DC cold

Type

Electronic

Frequency rating - min

50 Hz

Voltage rating

250 Vac, 32 Vdc (self certified)

Application

Electronic circuits

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

GDA-500MA-BUSS SMALL DIMENSION FUSE

Specifications and datasheets

Eaton Specification Sheet - GDA-500MA



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)