

Specifications



Photo is representative

Eaton HM25060-3MW12

Eaton Bussmann series HM power distribution fuse block, Multi-wire line-side lug, 60 A, 3-P, 10 kA RMS symm, Class K, Class H, Black, Box lug, 10 kA, 75 °C, Panel, DIN rail, 250 V, #2-14 AWG Cu, #2-8 AWG Al

General specifications

PRODUCT NAME	Eaton Bussmann series HM power distribution fuse block
CATALOG NUMBER	HM25060-3MW12
UPC	051712618489
PRODUCT LENGTH/DEPTH	4.2 in
PRODUCT HEIGHT	2.3 in
PRODUCT WIDTH	4.1 in
PRODUCT WEIGHT	0.59375 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	ARO European Pressure Equipment Directive (PED) 97 /23 EC



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	60 A
IMPULSE WITHSTAND VOLTAGE	10 kA RMS symmetrical
INTERRUPT RATING	10 kAIC
SHORT-CIRCUIT RATING	10 kA RMS symmetrical
TORQUE RATING	50 lb-in maximum
VOLTAGE RATING	250 V

General information

CONNECTION	Box lug
MOUNTING METHOD	DIN rail Panel
SPECIAL FEATURES	Multi-Wire Line-Side Lug

Physical details

COLOR	Black
CONDUCTOR MATERIAL RATED FOR	Both
CONDUCTOR TYPE	Stranded
FUSE TYPE	Class H Class K
NUMBER OF POLES	Three-pole
OPERATING TEMPERATURE - MAX	120 °C
OPERATING TEMPERATURE - MIN	120 °C
WIRE SIZE	#2-14 AWG Cu #2-8 AWG Al

Resources

CATALOGS	HM25060-3MW12~Fuse Blk, H 250V 60A 3P Bussmann series complete full line catalog no. 1007
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2204
MULTIMEDIA	Class H(K), J and R Power distribution fuse block overview Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - HM25060-3MW12

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.