

Eaton JM60030-1MW14

Catalog Number: JM60030-1MW14

Eaton Bussmann series JM modular fuse block, Multi-wire load-side lug, 30 A, 1P, 120°C, Class J, Black, Line: (1) 2-14 Cu, 2-8 Al|Load: (1) 8-14 Cu, (2) 12-14 Cu, (1) 8 Str Al, (1) 10 Sol Al, 200 kA, 75°C, Stranded, Panel|DIN rail, 600 V

General specifications



Photo is representative

Product Name

Eaton Bussmann series JM modular fuse block

Catalog Number

UPC
051712620567

Product Length/Depth

3.4 in

Product Height

2.3 in

Product Width

1.1 in

Product Weight

0.15833333 lb

Warranty

Not Applicable

Compliances

RoHS Compliant

Certifications

ARO
European Pressure Equipment Directive
(PED) 97 /23 EC

Electrical rating

Amperage Rating

30 A

Impulse withstand voltage

200 kA RMS symmetrical

Interrupt rating

200 kAIC

Short-circuit rating

200 kA RMS symmetrical

Torque rating

50 lb-in maximum

Voltage rating

600 V

Physical details

Color

Black

Conductor material rated for

Both

Conductor temperature rating

75 °C

Conductor type

Stranded

Fuse type

Class J

Number of Poles

Single-pole

Operating temperature - max

120 °C

Operating temperature - min

120 °C

General information

Connection

Box lug

Mounting method

Panel

DIN rail

Special features

Multi-Wire Load-Side Lug

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[JM60030-1MW14~1POLE J 600V30A PDFB 1-4](#)

[Bussmann series complete full line catalog no. 1007](#)

Multimedia

[Bussmann series Fuseology](#)

Specifications and datasheets

[Eaton Specification Sheet - JM60030-1MW14](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)