

Eaton LP-CC-25

Catalog Number: LP-CC-25

Eaton Bussmann series LP-CC fuse, Current-limiting time-delay fuse, Rejection style, 25 A, Dual, CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 20 kAIC at 300 Vdc|200 kAIC at 600 V, Melamine tube, 10, 600 V, 300 Vdc

General specifications

Product Name	Catalog Number
Eaton Bussmann series LP-CC fuse	LP-CC-25
UPC	EAN
051712180283	5027590446983
Product Length/Depth	Product Height
0.41 in	1.5 in
Product Width	Product Weight
0.41 in	0.15 lb
Warranty	Compliances
Not Applicable	CE Marked
	RoHS Compliant



Product specifications

Fuse indicator

Non-indicating

Special features

Rejection style

Interrupt rating

200 kAIC at 600 Vac

20 kAIC at 300 Vdc

Number of elements

Dual

Connection

Ferrule end x ferrule end

Response time

12 sec at 200%

Quantity

10

Material

Melamine tube

Amperage Rating

25 A

Type

Current-limiting time-delay fuse

Class

Class CC

Voltage rating

600 Vac, 300 Vdc

Application

Specialized circuits and industrial control

Packaging type

Standard

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

LP-CC-25~LOW PEAK CC TIME DELAY

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - LP-CC-25

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)