

Eaton LP-CC-4

Catalog Number: LP-CC-4

Eaton Bussmann series LP-CC fuse, Current-limiting time-delay fuse, Rejection style, 4 A, Dual, CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 20 kAIC at 150 Vdc|200 kAIC at 600 V, Melamine tube, Standard, 10, 600 V, 150 Vdc

General specifications

Product Name	Catalog Number
Eaton Bussmann series LP-CC fuse	LP-CC-4
UPC	EAN
051712180320	5704057051187
Product Length/Depth	Product Height
1.5 in	0.41 in
Product Width	Product Weight
0.41 in	0.15 lb
Warranty	Compliances
Not Applicable	CE Marked
	RoHS Compliant



Product specifications

Fuse indicator

Non-indicating

Special features

Rejection style

Interrupt rating

20 kAIC at 150 Vdc

200 kAIC at 600 Vac

Number of elements

Dual

Connection

Ferrule end x ferrule end

Response time

12 sec at 200%

Quantity

10

Material

Melamine tube

Amperage Rating

4 A

Type

Current-limiting time-delay fuse

Class

Class CC

Voltage rating

600 Vac, 150 Vdc

Application

Specialized circuits and industrial control

Packaging type

Standard

Resources

Catalogs

[LP-CC-4~LOW PEAK CC TIME DELAY](#)

[Bussmann series complete full line catalog no. 1007](#)

Multimedia

[Bussmann series Fuseology](#)

Specifications and datasheets

[Eaton Specification Sheet - LP-CC-4](#)

Technical service bulletins

[Datasheet - FNQ-30](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)