Product specifications

Eaton NON-3/4

Catalog Number: NON-3/4

Eaton Bussmann series NON fuse, Supplemental one-time fuse, Non current limiting, Light duty circuit locations, 0.75 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 125 Vdc|50 kAIC at 250 Vac, Standard, 10, 250 V, 125 Vdc

General specifications

Product Name Catalog Number

NON-3/4 Eaton Bussmann series NON fuse

UPC EAN

051712300148 5027590453721

Product Length/Depth **Product Height**

0.56 in 2 in

Product Width Product Weight

0.56 in 0.35 lb

Compliances Warranty **CE Marked**

Not Applicable



Electrical rating

Amperage Rating

0.75 A

Interrupt rating

50 kAIC at 125 Vdc 50 kAIC at 250 Vac

Voltage rating

250 Vac, 125 Vdc

Physical details

Packaging type

Standard

General information

Class

Class H

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Quantity

10

Special features

Non current limiting

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

NON-3/4~NON-3-4~BUSS ONE TIME FUSE

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - NON-3/4

Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia

