

# Specifications



Photo is representative



## Eaton RD80-3-508

Eaton Bussmann series RD non-fused rotary disconnect switch, Front/side handle operation, 600V, 80A, Non-fused disconnect switch

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series RD non-fused rotary disconnect switch
<b>CATALOG NUMBER</b>	RD80-3-508
<b>UPC</b>	051712402620
<b>PRODUCT LENGTH/DEPTH</b>	2.7 in
<b>PRODUCT HEIGHT</b>	2.97 in
<b>PRODUCT WIDTH</b>	2.55 in
<b>PRODUCT WEIGHT</b>	0.59 lb
<b>WARRANTY</b>	Not Applicable
<b>COMPLIANCES</b>	Not Applicable RoHS Compliant



Powering Business Worldwide

## Electrical rating

<b>AMPERAGE RATING</b>	80A
<b>VOLTAGE RATING</b>	600 V

## Physical details

<b>OPERATING TEMPERATURE - MAX</b>	70 °C
<b>OPERATING TEMPERATURE - MIN</b>	-20 °C

## Resources

<b>CATALOGS</b>	<a href="#">Bussmann series complete full line catalog no. 1007</a> <a href="#">RD80-3-508~Switch 80A Non-F 3P UL508</a>
<b>MULTIMEDIA</b>	<a href="#">Bussmann series Fuseology</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - RD80-3-508</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

