Specifications

Eaton REN-30

Eaton Bussmann series REN fuse, time lag, non current-limiting, Industrial and commercial structures, 30 A, Class H, Non-indicating, Ferrule end x ferrule end, 10 kAIC, Standard, 10, 250 V

General specifications

PRODUCT NAME	Eaton Bussmann series REN fuse
CATALOG NUMBER	REN-30
UPC	051712100304
PRODUCT LENGTH/DEPTH	2 in
PRODUCT HEIGHT	0.56 in
PRODUCT WIDTH	0.56 in
PRODUCT WEIGHT	0.55 lb
WARRANTY	Not Applicable
COMPLIANCES	Not Applicable

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	30 A
INTERRUPT RATING	10 kAIC
VOLTAGE RATING	250 V

Physical details

PACKAGING TYPE	Standard

General information

CLASS	Class H
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
QUANTITY	10
SPECIAL FEATURES	Super lag, time lag, non current-limiting

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007 REN-30~SUPER LAG RENEWABLE FUSE 30/250 Bussmann series full line catalog 1007, section 01-low voltage branch circuit fuses
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - REN-30

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.