

Specifications



Photo is representative



Eaton RES-40

Eaton Bussmann series RES fuse, time lag, non current-limiting, Industrial and commercial structures, 40 A, Class H, Non-indicating, Ferrule end x ferrule end, 10 kAIC at 250 Vac, Standard, 10, 600 V

General specifications

PRODUCT NAME	Eaton Bussmann series RES fuse
CATALOG NUMBER	RES-40
UPC	051712110402
EAN	5027590243995
PRODUCT LENGTH/DEPTH	0.78 in
PRODUCT HEIGHT	5.5 in
PRODUCT WIDTH	0.78 in
PRODUCT WEIGHT	0.29 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant



Powering Business Worldwide

Electrical rating

AMPERAGE RATING 40 A

INTERRUPT RATING 10 kAIC at 250 Vac

VOLTAGE RATING 600 V

General information

CLASS Class H

CONNECTION Ferrule end x ferrule end

FUSE INDICATOR Non-indicating

QUANTITY 10

SPECIAL FEATURES Super lag, time lag, non current-limiting

Physical details

PACKAGING TYPE Standard

Resources

CATALOGS [Bussmann series complete full line catalog no. 1007](#)

[RES-40~SUPER LAG RENEWABLE FUSE 40/600](#)

MULTIMEDIA [Bussmann series Fuseology](#)

SPECIFICATIONS AND DATASHEETS [Eaton Specification Sheet - RES-40](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.