

Telpower® 70-600A: 170Vdc Fuses

TPL

Specifications

Description: DC power distribution fuses for use with Telpower 15100, 15200, TP158HC and TPHCS disconnect systems. For replacement of Cooper Bussmann UBO fuses a TPL-TA adapter kit is necessary.

Dimensions: See Dimensions illustrations.

Ratings:

- Volts: — 170Vdc
- Amps: — 70-800A
- IR: — 100kA

Agency Information: CE, UL Recognized Guide JFHR2, File E56412 Bellcore.

Features and Benefits

- Current-limiting capability designed for DC power distribution systems
- Recognized branch circuit protection
- Complete system coordination capability
- Energy savings with low watts loss, low operating temperatures, and minimum I²t levels

Typical Applications

- Telecommunications power circuit protection

Catalog Numbers


| Catalog Numbers | Amp Rating |
|-----------------|------------|
| TPL-BA | 70 |
| TPL-BB | 80 |
| TPL-BC | 90 |
| TPL-BD | 100 |
| TPL-BE | 125 |
| TPL-BF | 150 |
| TPL-BG | 175 |
| TPL-BH | 200 |
| TPL-BK | 225 |
| TPL-BL | 250 |
| TPL-CN | 300 |
| TPL-CO | 350 |
| TPL-CR | 400 |
| TPL-CU | 450 |
| TPL-CV | 500 |
| TPL-CZ | 600 |
| TPL-CZH | 800 |

Accessories


- Spare fuse holders: TPSFH-LB (for TPL-B fuses)
TPSFH-LC (for TPL-C fuses)



Dimensions - in (mm)



TPL-BA, TPL-BD, TPL-BF, TPL-BH, TPL-BK, and TPL-BL



TPL-CN, TPL-CR, TPL-CV and TPL-CZ