

## Features

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished to a bright, easily maintainable finish that is modern, attractive, easy to clean, and that also enhances the surface's resistance to pitting and bacterial corrosion
- Designed for use with stainless steel Rigid / IMC, aluminum and galvanized conduit
- Two type 316 stainless steel bolts included
- No package quantity required



## Applications

Calbrite's stainless steel Split Ring Clamps are designed for mounting and securing conduit, horizontally or vertically, away from the wall or device in wash-down or corrosive environments when used with Calbrite's Mounting Plates and Extensions.

Part Number	Trade Size (in)	A Height (in)	B Length (in)	C Female Thread (in)	D Bolt Size (in)	Thickness (in)	Weight per each (in)
S60500SP00	½	1.16	2.22	0.38	#10 x ½	0.13	0.09
S60700SP00	¾	1.55	2.45	0.38	#10 x ½	0.13	0.11
S61000SP00	1	1.85	2.70	0.38	#10 x ½	0.14	0.14
S61200SP00	1 ¼	2.20	3.23	0.38	#10 x ½	0.14	0.16
S61500SP00	1 ½	2.55	3.50	0.38	#10 x ½	0.15	0.20
S62000SP00	2	3.05	3.92	0.38	#10 x ½	0.15	0.23
S62500SP00	2 ½	3.65	5.00	0.50	¼ x ¼	0.16	0.50
S63000SP00	3	4.40	5.76	0.50	¼ x ¼	0.21	0.75
S64000SP00	4	5.50	6.83	0.50	¼ x ¼	0.25	1.13

All dimensions are for informational purposes only \*Tolerances +/- 5%