

Rigid/intermediate grade conduit fittings

Conduit couplings

Rigid fittings

THREE-PIECE CONDUIT COUPLINGS – MALLEABLE IRON

Applications:

- Used to join two lengths of threaded conduit; couples conduit when conduit cannot be turned

Features:

- NPSM threads

Standard materials:

- Heavy duty casting
- Malleable iron

Standard finish:

- Zinc plated

Options:

Description

- Hot dip galvanized**Suffix**
.....**HDG**

Malleable iron (concrete tight)

UL File No. E-19189



Cat. #	Size	Unit qty.	Wt. lbs. per 100
190M	1/2"	25	23
191	3/4"	25	35
192	1"	10	60
193	1 1/4"	5	91
194	1 1/2"	5	167
195	2"	5	215
196	2 1/2"	2	430
197	3"	1	463
198	3 1/2"	1	655
199	4"	1	800
188	5"	1	1200
189	6"	1	2100

Not UL Listed.

THREE-PIECE CONDUIT COUPLINGS – ALUMINUM

Applications:

- Used to join two lengths of threaded conduit; couples conduit when conduit cannot be turned

Features:

- NPSM threads

Standard materials:

- Aluminum

Standard finish:

- Natural

Aluminum (concrete tight)

UL File No. E-19189



Cat. #	Size	Unit qty.	Wt. lbs. per 100
190SA	1/2"	25	7
191SA	3/4"	25	9
192SA	1"	10	18
193SA	1 1/4"	5	31
194SA	1 1/2"	5	41
195SA	2"	5	64
196SA	2 1/2"	2	95
197SA	3"	1	113
198SA	3 1/2"	1	201
199SA	4"	1	253

Rigid/intermediate grade conduit fittings

Conduit couplings

RIGID CONDUIT COUPLINGS – STEEL

Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

Standard material:

- Galvanized steel

UL File No. E-25501



Cat. #	Size	Unit qty.	Wt. lbs. per 100
RC50	1/2"	10	12
RC75	3/4"	10	18
RC100	1"	10	29
RC125	1 1/4"	5	38
RC150	1 1/2"	5	52
RC200	2"	5	69
RC250	2 1/2"	2	181
RC300	3"	1	220
RC350	3 1/2"	1	377
RC400	4"	1	298
RC500	5"	1	477
RC600	6"	1	684

RIGID CONDUIT COUPLINGS – ALUMINUM

Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

Features:

- Lightweight
- Easy to install
- Corrosion-resistant

Standard material:

- Aluminum

UL File No. E-324286



Cat. #	Size	Unit qty.	Wt. lbs. per 100
RC50SA	1/2"	50	6
RC75SA	3/4"	50	9
RC100SA	1"	50	13
RC125SA	1 1/4"	50	19
RC150SA	1 1/2"	50	23
RC200SA	2"	20	35
RC250SA	2 1/2"	12	68
RC300SA	3"	12	91
RC350SA	3 1/2"	12	108
RC400SA	4"	12	142
RC500SA	5"	1	242
RC600SA	6"	1	320