Thin wall conduit fittings (for EMT conduit)

Set screw type fittings - steel

SET SCREW TYPE FITTINGS

Features:

- Tri-head screws may be installed using a slotted, Phillips or Robertson head screwdriver
- Male hub threads NPSM
- Steel locknuts
- · Heavy steel walls
- Standard material: steel
- Standard finish: zinc plated
- · Concrete tight when taped

Straight connectors - insulated

UL File No. E-22132



1450

Cat. #	Size	Unit qty.	Wt. Ibs. per 100
1450	1/2"	50	9
1451	3/4"	25	14
1452	1″	20	23
1453	1 ¹ /4"	10	46
1454	1 ¹ / ₂ "	10	50
1455	2″	5	78
1456 & G	2 ¹ / ₂ "	2	130
1457 @ G	3"	1	140
1458 @ G	3 ¹ / ₂ "	1	180
1459 @G	4″	1	225

ATwo tightening screws.

GUL and cUL Listed for EMT, IMC and rigid conduit.

Straight connectors - non-insulated

UL File No. E-22132





450S

շ(Սլ)

(VL)

Cat. #	Size	Unit qty.	Wt. lbs. per 100
450S	1/2"	50	9
451	³ /4″	25	15
452	1″	20	23
453	1 ¹ /4"	10	46
454	1 ¹ /2″	10	50
455 A	2″	5	77
456 & G	21/2"	2	130
457 @G	3″	1	140
458 & G	31/2 "	1	180
459 & G	4″	1	225

456

ATwo tightening screws.

GUL and cUL Listed for EMT, IMC and rigid conduit.

Couplings

UL File No. E-22132





466

460

(VL)

Cat. #	Size	Unit qty.	Wt. Ibs. per 100
460	1/2"	50	9
461	3/4"	25	16
462	1″	20	23
463 B	11/4"	10	42
464 B	11/2"	10	50
465 B	2″	5	77
466 BG	2 ¹ /2"	2	130
467 00	3″	1	140
468 BG	3 ¹ / ₂ "	1	240
460 B B	۵"	1	250

BFour tightening screws.

GUL and cUL Listed for EMT, IMC and rigid conduit.

Available in 7 colors Crouse-Hinds series painted EMT fittings consists of set screw, compression, insulated and noninsulated EMT fittings. Although red is the most commonly used, other colors offered include white, blue, green, yellow, black, and orange. These can also be used in architectural design, to better match look and feel to suit architectural specification and preference. Red White Blue Yellow Green Black Orange

Part number example:						
450SGreen						
-						
Non-insulated Set screw connector		Color				
1/2″	450S	Red				
3/4″	451	White				
1″	452	Blue				
1 ¹ / ₄ "	453	Yellow				
11/2"	454	Orange				
2″	455	Green				
21/2"	456	Black				
3″	457	To order, simply add the				
31/2 "	458	name of the color needed after the catalog number.				
4″	459					

