

# Thin wall conduit fittings (for EMT conduit)

Compression type fittings – steel

EMT fittings

## COMPRESSION TYPE FITTINGS – STEEL

### Applications:

Thin wall conduit fittings are used:

- To join EMT to a box or enclosure
- To couple two ends of EMT conduit

### Features:

- Compression type
- Threadless
- Male hub threads – NPSM
- Steel locknuts
- Heavy steel walls
- Standard material: steel
- Standard finish: zinc plated

### Concrete tight straight connectors – insulated


UL File No. E-22132



Cat. #	Size	Unit qty.	Wt. lbs. per 100
1650	1/2"	50	11
1651	3/4"	25	16
1652	1"	25	25
1653	1 1/4"	10	43
1654	1 1/2"	10	54
1655	2"	5	76
1656	2 1/2"	2	190
1657	3"	1	300
1658	3 1/2"	1	330
1659	4"	1	360

### Straight connectors – non-insulated

UL File No. E-22132



Cat. #	Size	Unit qty.	Wt. lbs. per 100
650S	1/2"	50	9
651S	3/4"	25	16
652	1"	25	25
653	1 1/4"	10	43
654	1 1/2"	10	54
655	2"	5	76
656	2 1/2"	2	190
657	3"	1	300
658	3 1/2"	1	280
659	4"	1	360

### Couplings

UL File No. E-22132



Cat. #	Size	Unit qty.	Wt. lbs. per 100
660S	1/2"	50	12
661S	3/4"	25	18
662	1"	25	27
663	1 1/4"	10	46
664	1 1/2"	10	63
665	2"	5	92
666	2 1/2"	2	250
667	3"	1	410
668	3 1/2"	1	390
669	4"	1	485

## Available in 7 colors

Crouse-Hinds series painted EMT fittings consists of set screw, compression, insulated and non-insulated EMT fittings. Although red is the most commonly used, other colors offered include white, blue, green, yellow, black, and orange. These can also be used in architectural design, to better match look and feel to suit architectural specification and preference.



Part number example:

**650S**Green

Non-insulated Straight connector	Color
1/2"	Red
3/4"	White
1"	Blue
1 1/4"	Yellow
1 1/2"	Orange
2"	Green
2 1/2"	Black
3"	
3 1/2"	
4"	

To order, simply add the name of the color needed after the catalog number.