

Eaton CSR63542

Catalog Number: CSR63542

Eaton Crouse-Hinds series Arktite CSR interlocked receptacle, 60A, Brass contacts, Non-fused, Style 2, 20 HP/40 HP, Krydon fiberglass-reinforced polyester, 1-1/4", 250-600 Vac

General specifications

Product Name	Catalog Number
Eaton Crouse-Hinds series Arktite CSR interlocked receptacle	CSR63542
	UPC
	782274215457
Product Length/Depth	Product Height
7.87 in	19.26 in
Product Width	Product Weight
7.78 in	17.55 lb



Certifications and compliances

Area classification

Ordinary/Non-Hazardous Locations

Standards type

NEC/CEC

NEMA Rating

3

4

4X

12

Ingress protection (IP) ratings

IP66

Product specifications

Amperage Rating

60A

Trade size

1-1/4"

Fusing

Non-fused

Voltage rating

250-600 Vac

Horsepower

20 hp/40 hp

Grounding style

Style 2

Material

Krydon fiberglass-reinforced polyester

Contact material

Brass

Resources

Catalogs

[Arktite CSR Nonmetallic Interlock Receptacles catalog page](#)

Certification reports

[Arktite CSR Nonmetallic Interlock Receptacles UL certification](#)

[Arktite CSR Nonmetallic Interlock Receptacles Canadian certification](#)

Installation instructions

[IF 1439 - CSR 30A and 60A Interlocked Receptacle](#)

[IF 1334 - CSR Interlocked Receptacle](#)

[IF 1440 - CSR 30A and 60A Interlocked Receptacle with Bussmann Fuses](#)

Specifications and datasheets

[Eaton Specification Sheet - CSR63542](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)