

DSD-SR horsepower rated selector switch 30A, 600V; front operated

Features:

- Lockout for 3-position switch, handle in either position, is standard

Certifications and compliances:

CEC:

- Class I, Groups C, D
- Class II, Groups E, F, G
- Class III
- Enclosure 3, 5, 12

Electrical ratings:

Maximum current – 30 amperes;
heavy duty A600 rating

Voltage	Horsepower ratings	
	3-phase	1-phase
120	3	1.5
240	7.5	3
480	10	5
600	10	5

Options:

Description	Suffix
• Lockout for 2-position switch, handle in either position	SX178

Note: Lockout is provided for 3-position switch. Back box sold separately.



Ordering information: For use with EDS back boxes

Switch function	Cat. #	Number of poles	Number of positions	Connecting Diagram
ON/OFF	DSD SR30120	1	2	1 3 5 7 9 11
	DSD SR30220	2	2	2 4 6 8 10 12
	DSD SR30320	3	2	1 3 5 7 9 11
	DSD SR30420	4	2	2 4 6 8 10 12
	DSD SR30520	5	2	1 3 5 7 9 11
	DSD SR30620	6	2	1 3 5 7 9 11
DOUBLE THROW without OFF	DSD SR30121	1	2	1 3 5 7 9 11
	DSD SR30221	2	2	2 4 6 8 10 12
	DSD SR30321	3	2	1 3 5 7 9 11
DOUBLE THROW without OFF with electrically isolated contacts	DSD SR30123	1	2	1 3 5 7 9 11
	DSD SR30223	2	2	2 4 6 8 10 12
	DSD SR30323	3	2	1 3 5 7 9 11
DOUBLE THROW with OFF	DSD SR30132	1	3	3 1 7 5 11 9
	DSD SR30232	2	3	2 3 1 6 7 5 11 9
	DSD SR30332	3	3	1 3 5 7 9 11
DOUBLE THROW with OFF and electrically isolated contacts	DSD SR30134	1	3	3 1 7 5 11 9
	DSD SR30234	2	3	4 2 3 8 6 5 11 9
	DSD SR30334	3	3	1 3 5 7 9 11



DSD-SR cover assembly
 (shown mounted to an EDS back box)