

Eaton EDS2229

Catalog Number: EDS2229

Eaton Crouse-Hinds series EDS snap switch control station, 20A, With switch, With one 3/4" hub, Feraloy iron alloy, 2, Two-gang, Single-pole, 2, 120-277V, Dead end, Single-pole, 3/4", 120-277 Vac

General specifications

Product Name	Catalog Number
Eaton Crouse-Hinds series EDS snap switch control station	EDS2229
	UPC
	782274763859
Product Length/Depth	Product Height
5.06 in	5.875 in
Product Width	Product Weight
7.19 in	17.16 lb

Certifications and compliances

Area classification

Hazardous/Classified Locations

Standards type

NEC/CEC

NEC hazardous rating

Class I, Division 1

Class I, Division 2

Class II, Division 1

Class II, Division 2

Class III

NEMA Rating

3

7

9

Product specifications

Enclosure type

With switch

Trade size

3/4"

Number Of Poles

Single-pole

Switch function

Single-pole

Number of gangs

Two-gang

Style

Dead end

Voltage rating

120-277 Vac

Amperage Rating

20A

Hub style

With one 3/4" hub

Number of devices

2

Number of pushbuttons

2

Primary voltage range

120-277V

Material

Feraloy iron alloy

Resources

Catalogs

[EDS and EDSX Fully Assembled Snap Switches catalog page](#)

Certification reports

[EDS and EFD Explosionproof Snap Switches UL certification - snap switches](#)

[EDS and EFD Explosionproof Snap Switches Canadian certification - snap switches](#)

EDS and EFD Explosionproof Snap Switches UL certification - industrial control panels and assemblies

EDS and EFD Explosionproof Snap Switches Canadian certification - industrial control panels and assemblies

Installation instructions

IF 242 - EDS and EDSC Control Stations

IF 328 - EDS, EFS, EDSC and EFSC Single- and Two-gang Device Bodies

Specifications and datasheets

Eaton Specification Sheet - EDS2229



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)