

F series service entrance heads and replacement covers

Applications:

F series service entrance heads are used:

- For overhead service entrance to buildings
- With threaded rigid, threadless rigid or threadless thin wall (EMT) conduit and rigid conduit masts

Features:

- Two types available: threaded rigid – threads to conduit; threadless rigid or EMT – clamps to conduit
- Available knockouts in covers allow use with variety of sizes and numbers of wires
- Simple construction and easy assembly
- Consists of only two pieces plus the insulating knockout cover
- Easy to install

Certifications and compliances:

- UL standard: 514B
- CSA standard: C22.2 No. 18

Standard material:

- Copper-free aluminum

Standard finish:

- Natural

Ordering information:

F service heads

Threaded rigid



1/2" size



3/4" to 2" size



2 1/2" to 4" size

Hub size	Number and diameter of cover knockouts	Cat. #
1/2"	6 - 9/32	F186
3/4"	2 - 3/8 and 3 - 13/32	F285
1"	2 - 7/16 and 3 - 1/2	F385
1 1/4"	2 - 27/64 and 3 - 5/8	F485
1 1/2"	2 - 27/64 and 3 - 5/8	F585
2"	2 - 7/8, 1 - 13/16, 1 - 11/16, 1 - 9/16 and 1 - 21/32	F686
2 1/2"	2 - 17/16, 1 - 17/32, 1 - 11/64, 1 - 61/64 and 1 - 55/64	F766
3"	2 - 17/16, 1 - 17/32, 1 - 11/64, 1 - 61/64 and 1 - 55/64	F866
3 1/2"	3 - 13/4, 1 - 17/16, 1 - 15/16 and 1 - 13/16	F966
4"	3 - 13/4, 1 - 17/16, 1 - 15/16 and 1 - 13/16	F1066

Overall dimensions – replacement covers for F series service heads

Cat. #	Dimensions
CF690	1 1/2" diameter
5 H	1 31/32" diameter
5 NS	2 13/64" diameter
5 NL	2 19/32" diameter
CF60	3 7/16" diameter
CF707	7 13/16" x 3 11/16"
CF708	10 1/4" x 4 3/4"

Clamp type

Threadless rigid or EMT



Hub size	Number and diameter of cover knockouts	Cat. #
3/4"	2 - 3/8 and 3 - 13/32	F235
1"	2 - 7/16 and 3 - 1/2	F335
1 1/4"	2 - 27/64 and 3 - 5/8	F435
1 1/2"	2 - 27/64 and 3 - 5/8	F535
2"	2 - 7/8, 1 - 13/16, 1 - 11/16, 1 - 9/16 and 1 - 21/32	F636