

Applications:

- Ideal for terminating rigid/IMC conduit through the walls of enclosures
- Designed for use indoors or outdoors with rigid and IMC conduit; specific applications include: food processing plants, distilleries, breweries, sewage disposal plants, chemical plants, paper processing mills and refineries

Features:

- Male thread is on the nut for a low profile, space saving fit
- Quick and easy when installing rigid conduit nipple between two existing enclosures
- Insulated throat provides smooth pulling surface
- Furnished with SG sealing gasket
- Hub fits standard knockouts; no special tools required

Certifications and compliances:

- UL and cUL Listed, File No. E-19189
- UL standard: 514B
- Certified by UL to CSA standard: C22.2 No. 18
- Suitable for wet locations

Standard materials:

- Body and nut – malleable iron
- Sealing ring – steel and rubber

Standard finishes:

- Body and nut – zinc electroplate
- Sealing ring – natural

Options:

- | | |
|---------------------------------|---------------|
| Description | Suffix |
| • Mechanically galvanized | HDG |

**Ordering information and dimensions:**

Cat. #	Hub size	Unit qty.	Wt. lbs. per 100	A	B
HUB1	1/2"	25	18	1.49"	1.30"
HUB2	3/4"	10	25	1.44"	1.54"
HUB3	1"	5	50	1.57"	1.78"
HUB4	1 1/4"	5	25	1.98"	2.16"
HUB5	1 1/2"	2	20	2.00"	2.37"
HUB6	2"	1	10	2.19"	2.93"
HUB7	2 1/2"	1	10	2.61"	3.56"
HUB8	3"	1	5	2.81"	4.18"
HUB9	3 1/2"	1	5	3.02"	4.64"
HUB10	4"	1	2	3.65"	5.21"

