

Liquidtight fittings

Stainless steel liquidtight accessories

SEALING GASKETS (ORDER SEPARATELY)

Applications:

- To form a raintight seal between a conduit fitting and the outside of a box

Features:

- Gasket is designed to provide superior sealing for customer applications
- Constructed of stainless steel to provide extreme durability in the most corrosive applications

Certifications and compliances:

- UL Listed
- cUL Listed




Standard materials:

- Ring – stainless steel
- Gasket – neoprene rubber

Standard finishes:

- Stainless steel – natural
- Neoprene rubber – natural



Trade size	Cat. #	Unit qty.	Wt. lbs. per 100	A	B	C
1/2"	SG1SS	50	50	1.125	0.813	0.188
3/4"	SG2SS	25	25	1.375	1.125	0.188
1"	SG3SS	25	25	1.625	1.313	0.188
1 1/4"	SG4SS	5	5	2.000	1.625	0.188
1 1/2"	SG5SS	5	5	2.250	1.875	0.188
2"	SG6SS	5	5	2.750	2.313	0.188

LOCKNUTS (ORDER SEPARATELY)

Applications:

- 316 stainless steel locknuts can be used with conduit or NPS threaded pipe

Features:


- Precision machined threads allow for easy installation
- Heavy stock thickness and specially designed tabs tighten securely and will not easily loosen even in the most severe applications

Standard material:

- Locknut – stainless steel

Standard finish:

- Stainless steel – natural



Trade size	Cat. #	Unit qty.	Wt. lbs. per 100	A	B	C	Threads/inch
1/2"	11SS	1000	2	1.313	0.250	0.190	14.000
3/4"	12SS	500	3	1.613	0.312	0.220	14.000
1"	13SS	500	5	1.863	0.380	0.260	11.500
1 1/4"	14SS	100	7	2.250	0.380	0.260	11.500
1 1/2"	15SS	100	10	2.562	0.438	0.270	11.500
2"	16SST	100	21	3.063	0.602	0.280	11.500

Liquidtight fittings

Liquidtight accessories

SELF-RETAINING PVC GASKET WITH STEEL RING

Applications:

- Used with locknuts in order to obtain watertight seals when connecting Liquidator™ fittings to an enclosure

Certifications and compliances:

- UL Listed (3/8" to 2")

Standard material:

- Gasket with steel ring – PVC

Standard finish:

- PVC – natural

UL File No. E-23223



Cat. #	Trade size	Unit qty.	Wt. lbs. per 100
SG1	3/8" - 1/2"	100	1
SG2	3/4"	50	2
SG3	1"	50	2
SG4	1 1/4"	25	2
SG5	1 1/2"	25	4
SG6	2"	25	3
SG7	2 1/2"	10	5
SG8	3"	10	10
SG9	3 1/2"	10	12
SG10	4"	10	10
SG11	5"	5	15
SG12	6"	5	22

COMBINATION COUPLINGS FOR COUPLING LIQUIDTIGHT TO THREADED RIGID/IMC CONDUIT

Applications:

- Used to couple liquidtight conduit to threaded rigid and IMC conduit

Certifications and compliances:

- UL Listed
- cUL Listed
- UL File No. E-19189

Standard materials:

- Body – malleable iron
- Ferrule – steel

Standard finish:

- Malleable iron – zinc plated



Cat. #	Trade size	Unit qty.	Wt. lbs. per 100
LTR38	3/8"	25	17
LTR50	1/2"	25	29
LTR75	3/4"	25	33
LTR100	1"	5	59
LTR125	1 1/4"	2	105
LTR150	1 1/2"	2	105
LTR200	2"	1	160

For 3/8" liquidtight to 1/2" rigid/IMC.

COMBINATION COUPLINGS FOR COUPLING LIQUIDTIGHT TO THREADED RIGID/IMC CONDUIT – GROUNDING TYPE ALUMINUM LUG

Applications:

- Used to couple liquidtight conduit to threaded rigid/IMC conduit
- Available with an aluminum grounding lug

Standard materials:

- Body – malleable iron
- Ferrule – steel
- Lug – aluminum

Standard finishes:

- Malleable iron – zinc plated
- Aluminum – natural



Cat. #	Trade size	Unit qty.	Wt. lbs. per 100
LTR38G	3/8"	25	24
LTR50G	1/2"	25	30
LTR75G	3/4"	25	35
LTR100G	1"	5	59
LTR125G	1 1/4"	5	81
LTR150G	1 1/2"	2	107
LTR200G	2"	1	162

For 3/8" liquidtight to 1/2" rigid/IMC.