

# Eaton BR2040L200R

Catalog Number: BR2040L200R

Eaton Eaton BR main lug loadcenter, No feed-thru lugs, includes BREQS125 hold-down screw, 200 A, C3R, Aluminum, NEMA 3R, Metallic, 25 kAIC, BWH, 40 Circuits, Twenty-four pole, 20 Spaces, Three-wire, Single-phase, 120/240V, #1 AWG-300 kcmil Cu/Al

## General specifications

Product Name	Catalog Number
Eaton BR main lug loadcenter	BR2040L200R
UPC	Product Length/Depth
786676447553	5.19 in
Product Height	Product Width
25 in	14.31 in
Product Weight	Warranty
15.5 lb	10 year
Certifications	Catalog Notes
UL 50 UL 67	Has notch for brhdk125 hold-down kit.



## Product specifications

### Number of spaces

20

### Special features

No feed-thru lugs, includes BREQS125 hold-down screw

### Interrupt rating

25 kAIC

### Phase

Single-phase

### Wire size

#1 AWG-300 kcmil Cu/Al

### Bus material

Aluminum

### Main circuit breaker

BWH

### Enclosure

NEMA 1

### Amperage Rating

200 A

### Enclosure material

Metallic

### Type

Main lug

### Cover

Cover included

### Used with

Type BR 1-inch breakers

### Number of wires

3

### Number of circuits

40

### Voltage rating

120/240V

### Box size

C3R

## Resources

### Brochures

Loadcenters and Circuit Breakers

Type BR Arc Fault Circuit Breakers and Loadcenters

### Catalogs

Eaton's Volume 1—Residential and Light Commercial

### Drawings

Dimensional Drawing - BR 1 LOADCENTER, MAIN LUG ONLY, OUTDOOR NEMA 3R, 120/240 VAC, 1 PHASE

### Installation instructions

Cutler-Hammer Type CH and BR Loadcenters - Instructions

### Specifications and datasheets

Eaton Specification Sheet - BR2040L200R



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)