

# Specifications



## Eaton CHR9N9NKNSU

Eaton pedestal mount metered, Ringless, Left/Pos 1: 5-20R2GFI Non-grd fault WR/TR, Center/Pos 2: 5-20R2GFI Non-grd fault WR/TR, Right/Pos 3: 6-20R2 Non-grd fault WR, Top, Surface mounted, Standard 4 circuit

Photo is representative



### General specifications

<b>PRODUCT NAME</b>	Eaton pedestal mount metered
<b>CATALOG NUMBER</b>	CHR9N9NKNSU
<b>UPC</b>	786689321512
<b>PRODUCT LENGTH/DEPTH</b>	8 in
<b>PRODUCT HEIGHT</b>	8 in
<b>PRODUCT WIDTH</b>	10 in
<b>PRODUCT WEIGHT</b>	24 lb
<b>CERTIFICATIONS</b>	UL 231 UL Listed file E163588

## Product specifications

<b>SPECIAL FEATURES</b>	Pedestal mount metered
<b>TYPE</b>	Ringless
<b>CIRCUIT BREAKER POSITION 1</b>	Non-ground fault
<b>CIRCUIT BREAKER POSITION 2</b>	Non-ground fault
<b>CIRCUIT BREAKER POSITION 3</b>	Non-ground fault
<b>RECEPTACLE CENTER</b>	NEMA5-20R2GFI
<b>RECEPTACLE LEFT</b>	NEMA5-20R2GFI
<b>RECEPTACLE RIGHT</b>	NEMA6-20R2
<b>FEED TYPE</b>	Top
<b>MOUNTING</b>	Surface
<b>NUMBER OF CIRCUITS</b>	4

## Resources

**SPECIFICATIONS AND DATASHEETS** [Eaton Specification Sheet - CHR9N9NKNSU](#)

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

