






Contender® CPS Factory Sealed 20 Amp Pin and Sleeve Receptacles

Explosionproof, Delayed Action

Class I, Division 1 and 2, Groups C, D

Does not intermate with
CPS 20 Amp Factory Sealed Pin
and Sleeve Receptacles

			Catalog Numbers † 20 Amp 125–250 Vac 1HP, 20 Amp @ 18 Vdc
	Type	Wire/Pole	
Cover Assemblies			
		Receptacle Only	CPS152R
		GFCI Cover, 5 mA Trip Setting †	GFS1
CPS152R	GFS1		
		Spring Cover Replacement Kit (Aluminum)	CPSCA
		NEMA 3RX Corrosion Resistance Kit	ULINE3RXKIT
CPSCA	ULINE3RXKIT	NEMA 4X Corrosion Resistance Kit	ULINEREC4XKIT
Plug			
		Pressure Terminals	CPP516
		2W, 3P Plug amperes match receptacle ratings	

† Aluminum receptacle cover and malleable iron EDS box. For aluminum box and receptacle cover, add suffix –SA.
‡ GFI units rated 20 Amp, 125 Vac.
Appleton CPP516 plug is UL Classified for use on Crouse-Hinds CPS receptacles. Appleton covers are UL Classified to mount on Crouse-Hinds EDS mounting bodies. Crouse-Hinds and ENP are registered trademarks of Cooper Crouse-Hinds.