

Contender® Series Factory Sealed Push Button Stations

Explosionproof, Dust-Ignitionproof

10 Amp, 600 Vac Max. for Heavy Duty Use Momentary Contact. Furnished with Internal Ground Screw.

Class I, Division 1, Groups C, D
Class I, Division 2, Groups B, C, D
Class II, Division 1 and 2, Groups E, F, G
Class III
NEMA 3, 7CD, 9EFG

Controls

CONTROLS: HAZARDOUS LOCATION CONTROL STATIONS AND SWITCHES

		Hub Size (Inches)	Description		Nameplate Marking	Catalog Number	
						Dead-End	Feed-Thru
1-Gang †							
	1/2	1 Circuit Universal		Start/Stop	EDS1184	EDSC1184	
	3/4				EDS2184	EDSC2184	
	1				EDS3184	EDSC3184	
	1/2	2 Circuits Universal		Start/Stop	EDS1190	EDSC1190	
	3/4				EDS2190	EDSC2190	
	1				EDS3190	EDSC3190	
Red Mushroom Head — Maintained Contact — Emergency Stop Nameplate							
	1/2	1 Circuit Universal		Emergency Stop	EDS1714	EDSC1714	
	3/4				EDS2714	EDSC2714	
	1				EDS3714	EDSC3714	
2-Gang †							
	1/2	2 Circuit Universal		Start/Stop	EDS1284	EDSC1284	
	3/4				EDS2284	EDSC2284	
	1				EDS3284	EDSC3284	
	1/2	4 Circuits Universal		Start/Stop	EDS1290	EDSC1290	
	3/4				EDS2290	EDSC2290	
	1				EDS3290	EDSC3290	

† Malleable Iron Body and Cover. For Aluminum Body and Cover, add suffix - SA.