

# EFDB™ Series Factory–Sealed Photocontrol

## Explosionproof, Dust-Ignitionproof

For use with Threaded Metal Conduit.

*Explosionproof Remote Photocontrol – Single Gang*  
**Class I, Groups B, C, D**  
**Class II, Groups, E, F, G**  
**Class III**

### Applications

- Factory-sealed control stations confine arcing of device within the enclosure, preventing ignition of atmospheres.
- Used in classified areas where flammable vapors, gases or highly combustible dusts are present.
- For installation in chemical and petrochemical plants, refineries and other process industries, or where corrosive elements are present.

### Features

- Finish is an epoxy powder coat for enhanced corrosion resistance.
- Corrosion-resistant stainless steel hex-head captive screws hold cover to body.
- Factory-sealed enclosure eliminates need for adding sealing fittings and compound at each conduit entrance (for Groups C & D applications).
- Accurately tapped, tapered hubs for tight, rigid joints and ground continuity.
- Smooth, rounded integral bushing in each hub protects conductor insulation.




Hub Size (Inches)	Voltage	Max Current (A)	Max VA	Catalog Number ①②	
				Dead End	Feed Through
1/2	120	8.3	1000	EFDB150PC120	EFDCB150PC120
3/4	120	8.3	1000	EFDB175PC120	EFDCB175PC120
1	120	8.3	1000	EFDB110PC120	EFDCB110PC120

### Replacement Parts for Remote Photocontrol

Voltage	Current (A)	Max VA	Catalog Number	
			Complete Cover Assembly	Photocontrol Only
120	8.3	1000	EFKB-PC120	PC120X
208-277	3.5	1000	EFKB-PC277	PC277X

### EFDB Single Gang



Hub Size (Inches)	Dimensions in Inches		
	A	B	C
1/2 & 3/4	5.38	6.13	.78
1	5.50	6.31	.94

Turn On 1 to 3 footcandles; Turn On/Turn Off ratio: 1:3, Temperature range: -30 °F through 140 °F.

For Class I, Group B, external seals must be installed at each conduit entrance.

① For 208-277 volt rating, change **120** suffix to **277**; current ratings become 3.5 A.

② Standard catalog number represents malleable iron body with aluminum cover. For aluminum body, add suffix **-A**.

Ⓜ CSA Certification only.