

Thruwall & Floor Seals

For New Installation

Type FSK Dimensional Data:

Steel Pipe or Conduit Nom I.D. O.D.		Dimensions in Inches Cast Iron Pipe Nom I.D. O.D.		Copper Tubing Nom I.D. O.D.		Minimum Wall Thickness (Inches)	Catalog Number		
							Fitting Complete with Sealing Assembly	Fitting Only**	Sealing Assembly* Only†
$\frac{3}{8}$	.675			$\frac{3}{8}$	.500		FSK-10-68		FSK-68-25
$\frac{1}{2}$	.840			$\frac{1}{2}$	.625	$\frac{3}{4}$	FSK-10-88	FSK-1020	FSK-88-25
$\frac{3}{4}$	1.050			1	1.125		FSK-10-113		FSK-113-25
1	1.315			$1\frac{1}{4}$	1.375		FSK-10-138		FSK-138-25
$1\frac{1}{4}$	1.660			$1\frac{1}{2}$	1.625	$4\frac{1}{16}$	FSK-20-166	FSK-2030	FSK-166-35
$1\frac{1}{2}$	1.900			$1\frac{3}{4}$	1.875		FSK-20-193		FSK-193-35
	2.000			2	2.125		FSK-20-213		FSK-213-35
2	2.375	2	2.500	$2\frac{1}{4}$	2.375		FSK-20-250		FSK-250-35
$2\frac{1}{2}$	2.875	2	2.625	$2\frac{1}{2}$	2.625	$4\frac{1}{4}$	FSK-30-263	FSK-3040	FSK-263-45
	3.000	2	2.750				FSK-30-288		FSK-288-45
3	3.500						FSK-30-313		FSK-313-45
							FSK-30-350		FSK-350-45
$3\frac{1}{2}$	4.000	3	3.660			$4\frac{3}{4}$	FSK-40-366	FSK-4050	FSK-366-55
		3	3.800				FSK-40-380		FSK-380-55
4	4.500	3	3.960				FSK-40-410		FSK-410-55
							FSK-40-450		FSK-450-55
$4\frac{1}{2}$	5.000	4	4.800				FSK-60-480		FSK-480-80
	5.250	4	5.000				FSK-60-506		FSK-506-80
	5.500						FSK-60-530		FSK-530-80
5	5.563					5	FSK-60-563	FSK-6070	FSK-563-80
	6.000						FSK-60-610		
6	6.500						FSK-60-663		FSK-663-80
	6.625								

Thruwall Seals for LARGE SIZE MECHANICAL PIPES up to 14" O.D. are listed on Page SA9.

Grounding connection on one end can be furnished if required. See catalog page QA14 for ordering information. Ground Lug must be ordered on separate line immediately following FSK.

* Oversize sleeve can be ordered to accommodate wall thickness over 14". To order, specify actual wall thickness (not desired sleeve length).

** "Fitting Only" consists of the following parts, malleable or ductile iron bodies, oversize sleeve and sealing rings. (Except FSK 60 Series.)

†Furnished with a "Sealing Assembly" consisting of the following parts: pressure clamp, hex head cap screws, pressure rings and sealing grommet.

•A set of pressure rings and sealing grommet only is available separately.