

Pipe Straps

For Rigid Conduit & IMC

Type 14-S

Use: To support Rigid Conduit and IMC.

Features: Snap type - double ribbed

Material/Finish: Steel/Zinc Plated


Applicable Third Party Standards:

Fed. Spec: FF-S-760


Note:

2½" through 4" sizes also suitable for EMT.

Trade Size (inches)	Steel Straps Catalog Number	Dimensions in Inches			Minimum Recommended Bolt Dia.
		A	B	C	
½	14-50S	2⅞	1⅞ ₁₆	¾	¼
¾	14-75S	2⅞ ₁₆	1⅞ ₁₆	¾	¼
1	14-100S	2¾	1⅞ ₁₆	¾	¼
1¼	14-125S	3½	1⅞ ₈	1	⅝ ₁₆
1½	14-150S	3⅞	1⅞ ₁₆	1⅞	⅜
2	14-200S	4¾	2⅞	1¼	⅜
2½	14-250S	6⅞ ₁₆	2⅞	1¼	½
3	14-300S	6¾	3	1¼	½
3½	14-350S	7⅞	3⅞ ₁₆	1½	⅝ ₈
4	14-400S	8⅞	3⅞ ₁₆	1½	⅝ ₈



Type 14-S



Type THR

Use: To support Rigid Conduit and IMC.

Features: Snap type - double ribbed

Material/Finish: Steel/Zinc Plated

Third Party Certification:



CSA Certified: 104691

½" through 2" sizes only

Applicable Third Party Standards:

CSA C22.2 No.18

Fed. Spec: FF-S-760


Note:

2½" through 4" sizes also suitable for EMT.

Trade Size (inches)	Steel Straps Catalog Number	Dimensions in Inches			Minimum Recommended Bolt Dia.
		A	B	C	
½	THR-50S	1¾	2¼	⅝	⅜ ₁₆
¾	THR-75S	1 ²⁷ / ₃₂	2⅞ ₁₆	¾	⅜ ₁₆
1	THR-100S	2⅞ ₁₆	2⅞ ₁₆	2 ²³ / ₃₂	¼
1¼	THR-125S	2 ¹⁵ / ₁₆	3⅞	2 ²³ / ₃₂	¼
1½	THR-150S	3 ⁵ / ₃₂	3 ¹⁵ / ₁₆	2 ²³ / ₃₂	¼
2	THR-200S	4¼	5	2 ²³ / ₃₂	¼
2½	THR-250S	4 ¹¹ / ₁₆	5 ²³ / ₃₂	1	⅝ ₁₆
3	THR-300S	5 ¹¹ / ₁₆	6¾	1	⅝ ₁₆
3½	THR-350S	6⅞ ₁₆	7⅞ ₁₆	1	⅝ ₁₆
4	THR-400S	6 ²⁷ / ₃₂	7 ¹³ / ₁₆	1	⅝ ₁₆



Type THR



Type 14-G

Use:

To support Rigid Conduit and IMC.

Material/Finish:

Malleable Iron/Hot Dipped Galvanized

Third Party Certification:



CSA Certified: 009795.

Applicable Third Party Standards:


CSA: C22.2 No.18

Fed. Spec: FF-S-760

Note:

2½" through 4" sizes also suitable for EMT.

Malleable Straps Catalog Number	Conduit Size Inches	Dimensions in Inches			Minimum Recommended Bolt Dia.
		A	B	C	
14-18G	⅞	1 ¹⁵ / ₁₆	½	½	#10
14-25G	¾	1 ¹⁹ / ₃₂	1 ⁹ / ₃₂	⅞	¼
14-38G	⅝	1¾	⅞	¾	¼
14-50G	½	2¼	2 ⁹ / ₃₂	1 ⁹ / ₁₆	¼
14-75G	¾	2⅞ ₁₆	¾	1 ⁷ / ₃₂	¼
14-100G	1	3⅞ ₁₆	1 ⁹ / ₁₆	1½	¼
14-125G	1¼	3 ¹¹ / ₁₆	⅞	1⅞	⅜
14-150G	1½	6¼	1	2⅞	⅜
14-200G	2	5⅞ ₁₆	1⅞	2⅞ ₁₆	½
14-250G	2½	5 ⁵ / ₁₆	1⅞	3⅞ ₁₆	½
14-300G	3	7⅞ ₁₆	1⅞	3⅞ ₁₆	½
14-350G	3½	8⅞ ₁₆	1 ¹³ / ₁₆	4⅞	⅝
14-400G	4	8 ¹¹ / ₁₆	2	5	⅝
14-500G	5	10 ⁹ / ₁₆	2¾	6½	⅝
14-600G	6	12½	3⅞	7½	1



Type 14-G

