



UNIVERSAL BEAM CLAMP, THICK FLANGE, PLAIN, 3/8" ROD, 1 1/4" MAX FLANGE

CATALOG NUMBER

3100037PL



CERTIFICATIONS



FEATURES

Universal beam clamp for thick beams

PRODUCT ATTRIBUTES

Material: Cast Iron

Finish: Plain

Rod Size: 3/8"

Flange Thickness: 1 1/4" Max

A: 1"

Torque: 5 ft lb


Static Load 1: 500 lb

Static Load 2: 250 lb

ADDITIONAL PRODUCT DETAILS

Setscrew must be tightened and torqued onto the sloped side of the I-beam.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER