



## Catalog No. TC35362R

**Description: 60A 3P DBL THR N3R 600V NONFUSE**

**UPC No 783164337389**

**Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Double Throw**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Suitable for use as transfer equipment in standby systems in accordance with Article 702 of the National Electrical Code. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). 60/75 C conductor rating. Full cover interlocks. TC35362R



Representative Image

### Descriptors

Category	Double Throw
GO Schedule	SB

### Specifications

Voltage	600 AC
Amperage	60 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 3R (Outdoor)
Options	None
Wire Range (Cu/Al)	14-4 (Cu)
240 Vac, NEC Std, 3-ph	10.0 hp
480 Vac, NEC Std, 3-ph	10.0 hp
600 Vac, NEC Std, 3-ph	10.0 hp
GSA Compliance	Yes

### Classifications

cUL Listed	Yes
UL Listed	Yes

### Dimensions

Height	20.8 in
Depth	6.3 in
Width	11.4 in
Weight	21.0 lb



