

Catalog No. TC35367R



Description 800A 3P DBL THR N3R 600V NONFUSE

UPC No 783164486223

Products > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Double Throw

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Suitable for use as transfer equipment in standby systems in accordance with Article 702 of the National Electrical Code.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- 60/75°C conductor rating.
- Full cover interlocks.

Specifications

Descriptors

Category	Double Throw
GO Schedule	SB

Specifications

Voltage	600 AC
Amperage	800 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 3R (Outdoor)
Wire Range (Cu/Al)	(3) 250 - (3) 500 (Cu/Al)
240 Vac, NEC Std, 3-ph	125.0 hp
480 Vac, NEC Std, 3-ph	250.0 hp
600 Vac, NEC Std, 3-ph	350.0 hp
GSA Compliance	No

Classifications

UL Listed	Yes
-----------	-----

Dimensions

Height	63.8 in
Depth	8.9 in
Width	27.0 in

Dimensions

Weight	175.0 lb
--------	----------

Publications

Title	Publication No.	Publication Type
Outline Drawing, 400-800A Double Throw	10103091SH143	Drawings-Outline and Dimensional
Outline Drawing, 400-800A Double Throw		

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, time current curves, CSI Specifications and promotional literature.