



Representative Image

Catalog No. TG3221R**Description: 30A 2P GD N3R 240V SAFETY SWITCH****UPC No 783164008487****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty**

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TG3221R

Descriptors

Category

General Duty

Specifications

Amperage	30 A
Poles	2
Wires	3
Fusing	Fusible
Enclosure	NEMA 3R (Outdoor)
Wire Range (Cu/Al)	12-8 AL 14-8 CU
240 Vac, NEC Std, 1-ph	1.5 hp
240 Vac, Time Delay, 1-ph	3.0 hp
250 Vdc	5.0 hp
GSA Compliance	Yes

Classifications

cUL Listed	Yes
UL Listed	Yes

Dimensions

Height	9.8 in
Depth	3.3 in
Width	6.4 in
Weight	6.0 lb

