



Catalog No. TG4321

Description: 30A 3P GD N1 240V SWITCH

UPC No 783164008630

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TG4321



Representative Image

Descriptors

Category	General Duty
----------	--------------

Specifications

Amperage	30 A
Poles	3
Wires	4
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Wire Range (Cu/Al)	12-8 AL 14-8 CU
240 Vac, NEC Std, 1-ph	1.5
240 Vac, NEC Std, 3-ph	3
240 Vac, Time Delay, 1-ph	3
240 Vac, Time Delay, 3-ph	7.5
250 Vdc	5
GSA Compliance	Yes

Classifications

cUL Listed	Yes
UL Listed	Yes

Dimensions

Height	10.3
Depth	3.3
Width	6.4
Weight	5



