



Representative Image

### Catalog No. TG4323

Description: 100A 3P GD N1 240V FUSIBLE SW

UPC No 783164008678

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TG4323

#### Descriptors

Category	General Duty
----------	--------------

#### Specifications

Amperage	100 A
Poles	3
Wires	4
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Wire Range (Cu/Al)	10-1/0
240 Vac, NEC Std, 1-ph	7.5
240 Vac, NEC Std, 3-ph	15
240 Vac, Time Delay, 1-ph	15
240 Vac, Time Delay, 3-ph	30
250 Vdc	20
GSA Compliance	Yes

#### Classifications

cUL Listed	Yes
UL Listed	Yes

#### Dimensions

Height	21.3
Depth	4.9
Width	9.4
Weight	17



